



CHESTNUT
P R O D U C T S

SAFETY DATA SHEET
Finishing Oil

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Finishing Oil

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Air drying paint/lacquer product for interior use.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Chestnut Products
PO BOX 260,
Stowmarket,
IP14 9BX
+44 (0) 1473 890118
+44 (0) 1473 206522
mailroom@chestnutproducts.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0)1473 425878 (09:00-17:00 Mon- Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xn; R65, R48/20/21/22. N; R51/53. R10, R66, R67

2.2. Label elements

Pictogram



Signal word

Danger

Finishing Oil

| | |
|---|---|
| Hazard statements | <p>H226 Flammable liquid and vapour.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> |
| Precautionary statements | <p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P260 Do not breathe vapour/spray.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.</p> <p>P331 Do NOT induce vomiting.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with national regulations.</p> |
| Supplemental label information | <p>EUH066 Repeated exposure may cause skin dryness or cracking.</p> |
| Contains | <p>Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics, Naphtha (petroleum), hydrodesulfurized heavy <0.1% benzene, Naphtha (petroleum), hydrotreated heavy <0.1% benzene</p> |
| Supplementary precautionary statements | <p>P240 Ground/bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P261 Avoid breathing vapour/spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTER/doctor if you feel unwell.</p> <p>P314 Get medical advice/attention if you feel unwell.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P391 Collect spillage.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> |

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Finishing Oil

| | | |
|---|----------------------|--|
| Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics | | 50 - 100% |
| CAS number: — | EC number: 919-446-0 | REACH registration number: 01-2119458049-33-XXXX |
| Classification | | Classification (67/548/EEC or 1999/45/EC) |
| Flam. Liq. 3 - H226 | | Xn; R65. N; R51/53. R10, R67 |
| STOT SE 3 - H336 | | |
| Asp. Tox. 1 - H304 | | |
| Aquatic Chronic 2 - H411 | | |
| Naphtha (petroleum), hydrodesulfurized heavy <0.1% benzene | | 5 - <10% |
| CAS number: 64742-82-1 | EC number: 265-185-4 | |
| Classification | | Classification (67/548/EEC or 1999/45/EC) |
| Flam. Liq. 3 - H226 | | T; R48/23/24/25. Xn; R65. N; R51/53. R10, R66, R67 |
| STOT SE 3 - H336 | | |
| STOT RE 1 - H372 | | |
| Asp. Tox. 1 - H304 | | |
| Aquatic Chronic 2 - H411 | | |
| Naphtha (petroleum), hydrotreated heavy <0.1% benzene | | 1 - <2.5% |
| CAS number: 64742-48-9 | EC number: 265-150-3 | |
| Classification | | Classification (67/548/EEC or 1999/45/EC) |
| Asp. Tox. 1 - H304 | | Xn; R65 |
| Naphtha (petroleum) Hydrotreated Heavy <0.1% benzene | | 1 - <2.5% |
| CAS number: 64742-48-9 | EC number: 265-150-3 | |
| Classification | | Classification (67/548/EEC or 1999/45/EC) |
| Asp. Tox. 1 - H304 | | Xn; R65. R66 |
| Xylene | | 0.25 - <0.5% |
| CAS number: 1330-20-7 | EC number: 215-535-7 | REACH registration number: 01-2119488216-32-XXXX |
| Classification | | Classification (67/548/EEC or 1999/45/EC) |
| Flam. Liq. 3 - H226 | | Xn; R20/21. Xi; R38. R10 |
| Acute Tox. 4 - H312 | | |
| Acute Tox. 4 - H332 | | |
| Skin Irrit. 2 - H315 | | |

Finishing Oil

| | |
|---|--|
| Mesitylene | 0.025 - <0.25% |
| CAS number: 108-67-8 | EC number: 203-604-4 |
| Classification Flam. Liq. 3 - H226 STOT SE 3 - H335 Aquatic Chronic 2 - H411 | Classification (67/548/EEC or 1999/45/EC) Xi; R37. N; R51/53. R10 |
| Ethylbenzene | 0.025 - <0.25% |
| CAS number: 100-41-4 | EC number: 202-849-4 |
| Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 STOT RE 2 - H373 Asp. Tox. 1 - H304 | Classification (67/548/EEC or 1999/45/EC) F; R11. Xn; R65, R20, R48/20/21/22 |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|-----------------------------------|---|
| General information | Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel. |
| Inhalation | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. Get medical attention. |
| Ingestion | Rinse mouth thoroughly with water. Do not induce vomiting. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately. |
| Skin contact | Wash skin thoroughly with soap and water. |
| Eye contact | Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues. |
| Protection of first aiders | First aid personnel should wear appropriate protective equipment during any rescue. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Inhalation | A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect. |
| Ingestion | Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. A single exposure may cause the following adverse effects: Irritation. Nausea, vomiting. |
| Skin contact | Prolonged and frequent contact may cause redness and irritation. |
| Eye contact | May cause temporary eye irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

Finishing Oil

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Contains Hydrocarbons. The product is immiscible with water and will spread on the water surface.

Hazardous combustion products Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

Protective actions during firefighting Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate area. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Wear protective clothing as described in Section 8 of this safety data sheet. Promptly remove any clothing that becomes contaminated.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Wear protective clothing as described in Section 8 of this safety data sheet. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Do not empty into drains. For waste disposal, see Section 13. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Finishing Oil

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Handle all packages and containers carefully to minimise spills. Do not handle broken packages without protective equipment. Keep container tightly sealed when not in use. Avoid discharge to the aquatic environment. Do not reuse empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store locked up. Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep containers upright. Protect containers from damage.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

Mesitylene

Long-term exposure limit (8-hour TWA): WEL 25 ppm 125 mg/m³

Ethylbenzene

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Xylene (CAS: 1330-20-7)

Finishing Oil

| | |
|-------------|---|
| DNEL | Workers - Inhalation; Short term local effects: 289 mg/m ³ |
| | Workers - Inhalation; Short term systemic effects: 289 mg/m ³ |
| | Workers - Inhalation; Long term systemic effects: 77 mg/m ³ |
| | Workers - Dermal; Long term systemic effects: 180 mg/kg/day |
| | Consumer - Inhalation; Short term local effects: 174 mg/m ³ |
| | Consumer - Inhalation; Short term systemic effects: 174 mg/m ³ |
| | Consumer - Inhalation; Long term systemic effects: 14.8 mg/m ³ |
| | Consumer - Dermal; Long term systemic effects: 108 mg/kg/day |
| | Consumer - Oral; Long term systemic effects: 1.6 mg/kg/day |
| PNEC | - Fresh water; 0.327 mg/l |
| | - Marine water; 0.327 mg/l |
| | - Intermittent release; 0.327 mg/l |
| | - STP; 6.58 mg/l |
| | - Sediment (Freshwater); 12.46 mg/kg |
| | - Sediment (Marinewater); 12.46 mg/kg |
| | - Soil; 2.31 mg/kg |

Mesitylene (CAS: 108-67-8)

| | |
|-------------|--|
| DNEL | Workers - Inhalation; Short term systemic effects: 100 mg/m ³ |
| | Workers - Inhalation; Long term local effects: 100 mg/m ³ |
| | Workers - Inhalation; Long term systemic effects: 100 mg/m ³ |
| | Workers - Dermal; Long term systemic effects: 16171 mg/kg/day |
| | Consumer - Inhalation; Short term local effects: 19.4 mg/m ³ |
| | Consumer - Inhalation; Short term systemic effects: 29.4 mg/m ³ |
| | Consumer - Dermal; Long term systemic effects: 9512 mg/kg/day |
| | Consumer - Oral; Long term systemic effects: 15 mg/kg/day |
| PNEC | - Fresh water; 0.101 mg/l |
| | - Marine water; 0.101 mg/l |
| | - Intermittent release; 0.101 mg/l |
| | - STP; 2.02 mg/l |
| | - Sediment (Freshwater); 7.86 mg/kg |
| | - Sediment (Marinewater); 7.86 mg/kg |
| | - Soil; 1.34 mg/kg |

8.2. Exposure controls

| | |
|---|--|
| Appropriate engineering controls | Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients. |
| Eye/face protection | Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Wear chemical splash goggles. |
| Hand protection | For users with sensitive skin, it is recommended that suitable protective gloves are worn. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. |
| Other skin and body protection | Wear appropriate clothing to prevent repeated or prolonged skin contact. |
| Hygiene measures | Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. |
| Respiratory protection | If ventilation is inadequate, suitable respiratory protection must be worn. |
| Environmental exposure controls | Keep container tightly sealed when not in use. Avoid release to the environment. |

Finishing Oil

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Appearance | Viscous liquid. |
| Colour | Yellow. or Orange. |
| Odour | Characteristic. |
| Odour threshold | Not available. |
| pH | Not available. |
| Melting point | Not available. |
| Initial boiling point and range | Not available. |
| Flash point | 38°C |
| Evaporation rate | Not available. |
| Upper/lower flammability or explosive limits | Not available. |
| Vapour pressure | <110 kPa @ 25°C |
| Vapour density | Not available. |
| Relative density | 0.8-0.9 |
| Solubility(ies) | Insoluble in water. |
| Partition coefficient | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition Temperature | Not available. |
| Viscosity | Not applicable. |
| Explosive properties | Not considered to be explosive. |
| Oxidising properties | Does not meet the criteria for classification as oxidising. |

9.2. Other information

| | |
|--------------------------|--------------------------|
| Other information | No information required. |
|--------------------------|--------------------------|

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|--|
| Reactivity | See the other subsections of this section for further details. |
|-------------------|--|

10.2. Chemical stability

| | |
|------------------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions. |
|------------------|---|

10.3. Possibility of hazardous reactions

| | |
|---|--|
| Possibility of hazardous reactions | The following materials may react strongly with the product: Oxidising agents. |
|---|--|

10.4. Conditions to avoid

Finishing Oil

Conditions to avoid Keep at temperature not exceeding 45°C/122°F. Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.

10.5. Incompatible materials

Materials to avoid Oxidising materials. Acids - oxidising.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance which may be potentially carcinogenic. IARC Group 2B Possibly carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs

Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Finishing Oil

| | |
|----------------------------|---|
| Aspiration hazard | Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs. |
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Inhalation | A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect. |
| Ingestion | Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. A single exposure may cause the following adverse effects: Irritation. Nausea, vomiting. |
| Skin contact | Repeated exposure may cause skin dryness or cracking. |
| Eye contact | May cause temporary eye irritation. |
| Route of entry | Ingestion Inhalation Skin and/or eye contact |
| Target organs | Central nervous system |

Toxicological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >15000 mg/kg, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >3400 mg/kg, Dermal, Rat REACH dossier information. Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LD₅₀ >13.1 mg/l, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Dose: 0.5 mL, 4 hours, Rabbit Erythema/eschar score: Very slight erythema - barely perceptible (1). Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

Carcinogenicity

Finishing Oil

Carcinogenicity NOAEC 690 ppm, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEC >300 ppm, Inhalation, Rat P REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity - development Developmental toxicity:, Maternal toxicity: - NOAEL: >5220 mg/m³, Inhalation, Rat No evidence of reproductive toxicity in animal studies.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed.

Naphtha (petroleum), hydrodesulfurized heavy <0.1% benzene

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit REACH dossier information. Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LD₅₀ >5610 mg/m³, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Repeated exposure may cause skin dryness or cracking.

Skin sensitisation

Skin sensitisation Buehler test - Guinea pig: Not sensitising. REACH dossier information. Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Based on available data the classification criteria are not met.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Two-generation study - NOAEC >20000 mg/m³, Inhalation, Rat P, F1 REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity - development Fetotoxicity:, Maternal toxicity: - NOAEL: 23900 mg/m³, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Finishing Oil

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 1 - H372 Causes damage to organs through prolonged or repeated exposure.

Target organs Central nervous system

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Acute toxicity - fish LL₅₀, 96 hours: 10-30 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: 10-22 mg/l, Daphnia magna

Chronic toxicity - fish early life stage NOELR, 28 days: 0.13 mg/l, Onchorhynchus mykiss (Rainbow trout)

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.372 mg/l, Daphnia magna

Naphtha (petroleum), hydrodesulfurized heavy <0.1% benzene

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Acute toxicity - fish LL₅₀, 96 hours: 8.2 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: 4.5 mg/l, Daphnia magna

Acute toxicity - aquatic plants EL₅₀, 72 hours: 3.1 mg/l, Selenastrum capricornutum

Chronic toxicity - fish early life stage NOELR, 14 days: 2.6 mg/l, Pimephales promelas (Fat-head Minnow)

Chronic toxicity - aquatic invertebrates NOELR, 21 days: 2.6 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Finishing Oil

Persistence and degradability The product is readily biodegradable.

Biodegradation Water - Degradation 74.7%: 28 days

Naphtha (petroleum), hydrodesulfurized heavy <0.1% benzene

Persistence and degradability The product is readily biodegradable.

Biodegradation Water - Degradation 77%: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Bioaccumulative potential No data available on bioaccumulation.

Naphtha (petroleum), hydrodesulfurized heavy <0.1% benzene

Bioaccumulative potential BCF: 10-2500, Estimated value.

12.4. Mobility in soil

Mobility The product is insoluble in water. Volatile liquid. The product contains organic solvents which will evaporate easily from all surfaces.

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Mobility The product is insoluble in water.

Surface tension 24.7 mN/m @ 25°C

Naphtha (petroleum), hydrodesulfurized heavy <0.1% benzene

Mobility The product is insoluble in water.

Adsorption/desorption coefficient Soil - log Koc: 1.78-2.36 @ 25°C Estimated value.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Naphtha (petroleum), hydrodesulfurized heavy <0.1% benzene

Finishing Oil

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

| | |
|------------------|------|
| UN No. (ADR/RID) | 1263 |
| UN No. (IMDG) | 1263 |
| UN No. (ICAO) | 1263 |
| UN No. (ADN) | 1263 |

14.2. UN proper shipping name

| | |
|--------------------------------|-------|
| Proper shipping name (ADR/RID) | PAINT |
| Proper shipping name (IMDG) | PAINT |
| Proper shipping name (ICAO) | PAINT |
| Proper shipping name (ADN) | PAINT |

14.3. Transport hazard class(es)

| | |
|-----------------------------|----|
| ADR/RID class | 3 |
| ADR/RID classification code | F1 |
| ADR/RID label | 3 |
| IMDG class | 3 |
| ICAO class/division | 3 |
| ADN class | 3 |

Transport labels



Finishing Oil

14.4. Packing group

| | |
|-----------------------|-----|
| ADR/RID packing group | III |
| IMDG packing group | III |
| ADN packing group | III |
| ICAO packing group | III |

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

| | |
|--|----------|
| EmS | F-E, S-E |
| ADR transport category | 3 |
| Emergency Action Code | •3Y |
| Hazard Identification Number (ADR/RID) | 30 |
| Tunnel restriction code | (D/E) |

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|-----------------------------|--|
| National regulations | Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits. |
| EU legislation | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC. |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Finishing Oil

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

| | |
|---|---|
| Classification procedures according to Regulation (EC) 1272/2008 | Asp. Tox. 1 - H304: STOT RE 2 - H373: STOT SE 3 - H336: : Calculation method. Aquatic Chronic 2 - H411: : Calculation method. Flam. Liq. 3 - H226: : Expert judgement. |
| Training advice | Read and follow manufacturer's recommendations. |
| Revision comments | Classification according to EC 1272/2008 (CLP). |
| Revision date | 26/05/2015 |
| Revision | 8 |
| Supersedes date | 13/06/2014 |
| SDS number | 2872 |
| Risk phrases in full | R10 Flammable. R11 Highly flammable. R20 Harmful by inhalation. R20/21 Harmful by inhalation and in contact with skin. R37 Irritating to respiratory system. R38 Irritating to skin. R48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. R48/23/24/25 Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. |
| Hazard statements in full | H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure. H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.